

- Drafts**
- BRS:
 - Pending
 - Active
 - L3: (9209) (serial nearl ata) sata
 - L4: (1623) (parallel nearl ata) pata
 - L5: (393) 3 same 4
 - L6: (9) buffer same 5
 - L7: (50) ("5649146") or ("5973512") or ("4250412") or ("4253059") or ("4306146") or ("2
 - Failed
 - Saved
 - S1: (40453) ata
 - S2: (684960) advanced nearl technology nearl attachment
 - S3: (718862) S1 S2
 - S4: (4470) serial near9 S3
 - S5: (6320) parallel near9 S3
 - S6: (546) S4 with S5
 - S7: (9) buffer with S6
 - S8: (82) ata nearl bridge
 - S11: (472) buffer with ata
 - S9: (82) S1 nearl bridge
 - S10: (2) buffer with S9
 - S14: (684) parallel near9 S1
 - S12: (12) bridge with S11
 - S13: (2) ("5995486") or ("20040252716").PN.
 - Favorites
 - Tagged (3)
 - UDC
 - Queue

 US-PGPUB;USPAT;USOCR;FPRS;EPO;JPO;DERWENT;IBM_TDB
☒ PurelsDefault operator: ☐ Highlight all hit terms initially
☒ BRS form ☒ IS&R form ☒ Image ☒ Text ☒ HTML

	U	Document ID	Issue Date	Pages	Title	Current OR	Current XRef	Retrieval Cla	Inventor	S	C	P	Im
1	<input type="checkbox"/>	<input checked="" type="checkbox"/> US 20030074515 A1	20030417	8	System for supporting both serial and parallel storage devices on	710/313	710/316		Resnick, Russell Alan	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	US
2	<input type="checkbox"/>	<input checked="" type="checkbox"/> US 20040252716 A1	20041216	64	Serial advanced technology attachment (SATA) switch	370/447	370/462; 710/309		Nemazie, Sam	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	US
3	<input type="checkbox"/>	<input checked="" type="checkbox"/> US 5995486 A	19991130	11	Flow control method and apparatus for cell-based	370/229	370/412		Iliadis, Ilias	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	US

☒ Hits ☒ Details ☒ HTML

Ready

CAP NUM: